



01948 667 600



info@securasound.co.uk



The Hollies, Chester rd,  
Whitchurch, SY13 1LZ

# Engineering data sheet



## 7549/M

### 2 Wire, colour, 1 way, Door Entry Kit

- **Contains:**

- 1 x 7549 Tab monitor
- 1 x 13K1 Video entry panel
- 1 x 6922.1 power supply

- **Main Features:**

- Entrance Panel can be flush or surface mounted.
- Monitor has 4.3" LCD Colour display
- Monitor is surface mounted

### Specifications

**System** 2 wire due Fili

**Controls** Capacitive buttons for door release, speech, self activation, auxiliary function, user control of brightness, volume and muting

**Monitor** High impact moulded plastic with high gloss white finish.

**Entrance Panel** Flush or surface mount, electro polished anodised aluminium.

**Power supply** Din rail or surface mount (mains connection required)

**Dimensions** Monitor 160mm wide, 180mm high, 45mm deep.

Entrance Panel 168mm high, 100mm wide, surface depth 37mm, flush depth 23mm + 12mm

PSU 142mm wide, 96mm high, 70mm deep

### General information

This colour video door entry kit has an attractive and modern look. It can be wired using copper Cat5e/6e cable configured to provide 2 cores. The Tab monitor has a 4.3" colour display, glass effect finish and capacitive technology with backlit touch buttons.

The entrance Panel can be flush or surface mounted. The Entrance Panel camera unit has a 12V DC lock output integral with the system connections.

The power supply requires a switched mains connection.