

AGT A EVO

HANDSET INTERCOM WITH SOFT-TOUCH BUTTONS, 1 PROGRAMMABLE AUX BUTTON AND 4 BUTTONS FOR INTERCOM CALLS, WHITE.

COMPATIBLE SYSTEMS



TECHNICAL DATA

| | |
|-----------------------------------|------------------|
| Dimensions (mm) | 116 x 190 x 44.5 |
| Power supply by BUS (V) | 15 ÷ 20 DC |
| Absorption by BUS (mA) | 30 |
| Consumption in stand-by mode (mA) | <0,5 |
| Operating temperature (°C) | +5 ÷ +40 |
| Protection rating (IP) | 30 |
| Colour | White |

Wall-mounted intercom with 3 main soft-touch buttons for door opening, programmable auxiliary control and ringtone adjustment/exclusion (with signaling LED when excluded). Suitable for multi-user systems as it allows up to 6 intercom calls and the sending of the "Panic" signal for the porter to call for help. It allows managing the "gate opener" function and displays the status of the gate controlled by means of a signaling LED. Prearranged for wall installation on horizontal and vertical 503 box and on round Ø 60 mm box.

FEATURES

- Handset with magnetic hang-up
- Concealed LED signal
- AUX2 for auxiliary functions and call to the porter
- Automatic door-opener function
- Suitable for multi-user systems with 6 Intercom calls
- Door-opener soft-touch button
- Programmable auxiliary soft-touch button
- Soft-touch button for ringtone adjustment/ exclusion with LED indicator when excluded
- Call forwarding to other extension
- "Panic" control for calling the porter
- Latch function (gate opener) for checking the status of external automation

ACCESSORIES



AGT KTA

Desktop stand. Plexiglass 10mm thick stand supplied with white RJ45 cable and terminal board cover with PMMA laminate - metallic grey

DIMENSIONS

