



01948 667 600



info@securasound.co.uk




The Hollies, Chester rd,  
Whitchurch, SY13 1LZ

# Engineering data sheet



## K40515.E

2 wire, colour, 1 way, video door entry kit 

- 40515 Tab5SUP Video monitor
- 40151 Entrance panel (1button)
- 40135 Audio/Video unit
- 40110 Power supply

### Specifications

**System** 2 wire due fili

**Monitor** Capacitive touch keypad with backlit symbols

**Entrance Panel** Flush/Surface mounted, back lit call button with white LED'S

**Power Supply** Din rail or surface mount (mains connection required)

**Dimensions** Monitor 148 mm wide,158mm high, 24.4mm deep (surface mount) 13.1mm deep (flush mount – using 40590 box)  
Entrance Panel – Surface mount 168mm high, 100mm wide, 37mm deep.

Entrance Panel-Flush mount 168mm high, 100mm wide, 23+12mm deep

Power supply 96mm high, 142mm wide, 70mm deep

### General information

This colour video door entry kit has an attractive and modern look. It is recommended that the kit is wired using copper Cat5e/6e cable configured to provide 2 cores as shown below.

The entrance panel as an anodised aluminium finish and can be surface or flush mounted with the back boxes provided.

The 40515 Tab5SUP monitor has an integrated wi-fi access to enable calls to be forwarded to a smart phone via the 'Vimar View' app, for control of the call.

The monitor has configurable video voicemail, multiple ringtones, adjustable audio and video settings and the option of a system contacts list and favourites menu for quick access.