## **Telephone Handset**

### EXPERIENCE

Entrotec has over 25 years of experience in the design and manufacture of vandal resistant door entry systems.

#### WARRANTY

Entrotec systems are renowned for their reliability and have a 2 year warranty on all Entrotec manufactured products as standard.

#### SUPPORT

Entrotec offer complimentary training courses and telephone support.

- H = 210mm W = 100mm D = 50mm
- High Impact White ABS Plastic
- Latching Privacy Switch with Illuminated LED
- Door Open Button with Illuminated LED
- Adjustable Call Tone Volume
- Optional Extension/ Accessories Available
- Optional Alarm Input Available

# **Technical Specification**

Privacy	Illuminated Red LED button to indicate privacy on Latch on/off (no timeout)	Power	Operational voltage 10-16VDC OmA during idling
	Muted call tone when privacy on	Power	189mA during call tone
Door Open	Large 20mm door release button	Consumption	9mA per lit LED (Privacy and/or Door Open)
	Illuminated Green LED button to indicate door open Anti "Lock-Down" feature as standard	Cable Note*	CW1308 4 pair minimum (leaves 1 spare core) *3 pair can be used if Door Open LED function omitted*
Call Tone	Pulsed tone with volume adjust feature as standard	Extension	Additional handsets can be fitted (up to 3 in total)
Volume	Adjustable from mute (on Privacy) to 84dB at 13.8VDC Adjustable by internal volume control		Optional extension Beacon available Optional extension Sounder/Beacon available
	(measurement taken – distance 100cm orientation 0 <sup>o</sup> )	Accessories	Inductive Coupler available for Hard of Hearing Handset Hook available for Physically Impaired Relay for triggering aux. equipment (pulsed with call tone) Timer for triggering aux. equipment (triggered by call tone)
		Note*	*All Extension equipment and Accessories sold separately*
Entrotec Limited www.entrotec.com			



www.entrotec.com Tel: +44(0) 1506 886230 Fax: +44(0) 1506 886233 saleshq@entrotec.co.uk Support: 0844 858 6370







ENTROTEC

DS008 - Rev 1